BAUWERK® Parquet

T +41 (0)71 747 74 74 F +41 (0)71 747 74 75 info@bauwerk.com

DECLARATION OF PERFORMANCE

IN ACCORDANCE WITH CONSTRUCTION PRODUCTS REGULATION (EU) NO. 305/2011 & 574/2014 AND

IN ACCORDANCE WITH THE SWISS CONSTRUCTION PRODUCTS LAW 933.0

DoP-No. 800 / CPR / 30.10.2019

1. Unique id	lentification c	ode of the	product type
--------------	-----------------	------------	--------------

Multi-layer parquet elements according to EN 13489:2002 (wood flooring) Triopark 14mm

- 2. Intended use(s) of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Floor covering for indoor use (to fully bond on substrate)
- 3. Name, registered trade name or registered trade mark and contact adress of the manufacturer in accordance with Articel 11, paragraph 5:

Bauwerk Parkett AG

Neudorfstrasse 49

CH-9430 St. Margrethen

- System or systems of assessment and verification of constancy of performance of the construction products as set out in Annex V:
 System 3
- In case of a declaration of performance concering a construction product covered by a harmonised standard: EN 14342;2013

regarding Formaldehyde- and Pentachlorphenole:	regarding reaction of fire:
eph - Entwicklungs- und Prüflabor Holztechnologie	ÖTI – Institut für Ökologie,
Zellescher Weg 24	Technik und Innovation
D-01227 Dresden	A-1050 Wien
(not. body 0766)	(not. body 0534)
or	
eco-INSTITUT GmbH	
Sachsenring 69	
D-50677 Köln	
(not. body 2097)	

regarding slip-resistance feature:		
eph - Entwicklungs- und Prüflabor Holztechnologie		
Zellescher Weg 24		
D-01227 Dresden		
(not, body 0766)		

6. Declared performance

Essential characteristics	Performance	
Reaction of fire	C _{ff} -s1	(to fully bond on substrate) (only Triopark oak smoked and beech unsteamed matt laquered)
	D _{fl} -s1	(to fully bond on substrate)
Emission of Formaldehyde	class E1	
Content of Pentachlorphenol	≤5 ppm	
Breaking strength	NPD	
Slip resistance	71 USRV (natural oiled)	44 USRV (matt laquered)
Thermal conductivity	~ 0.14 W / m*K	
Biological durability	Use class 1	

7. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Christian Steiner, Director Total Quality Management Bauwerk Boen Group

Parkett

Bauwerk Parkett AG CH-9430 St. Margrethen info@bauwerk.com www.bauwerk-parkett.com